



STAG™ TDS Technical Data Sheet



STAG PVC Cleaner

Product Code: 32-582-0818
Most Recent Revision Date: 19 March 2023

Product Description

A quick acting, solvent-based formulation designed to clean and prime rigid PVC pipes and fittings. For use on low and high-pressure pipes for effective removal of dirt, debris, oils and grease while keying surface for adhesive to bond to. The ideal cleaner when workmanship and integrity of the joint are a priority.

Applications

- Cleaning and priming PVC rigid pipes and fittings. Designed to work with STAG PVC Weld.
- Low and high-pressure pipes.
- Cleaning of HDPE and PP pipes (no priming effect).

Benefits

- Removes dirt, dust, oils and grease.
- Quick evaporation prevents excessive softening of PVC.
- Provides a key to improve the binding of adhesives prior to jointing.
- Can be used as a general surface cleaning solvent including on HDPE and PP pipes.

Specification

Property	Unit	Value	Test Method/Standard
Appearance	-	Clear	Visual
Specific Gravity:	g/cm ³	0.80 - 0.84	SG Cup
Shelf life	Months	12	When stored unopened, in original package between 5 and 40°C in a dry and frost proof area

Packaging

Standard Pack Sizes: 500ml tin.

Application Information

Surface preparation: Remove loose debris, dirt, oil and grease from pipe to be cleaned.

Mixing: Shake for 30sec before use.

Application Method:

- Apply STAG PVC Cleaner to a clean, dry lint-free cloth or paper towel; wipe areas to be joined thoroughly.
- Ensure both surfaces of the joint adhesion are properly clean. Repeat above step if necessary.
- Reseal container tightly when not in use.



STAG™

TDS Technical Data Sheet

- Allow a minimum of 1 minute before application of STAG PVC Weld.
- Ensure solvent has evaporated from cloth or paper towel before disposal (flammable).
- **NOT SUITABLE FOR USE ON:** Flexible or highly plasticized PVC.

Application Temperatures: 5 – 40°C

Precautions:

- Ensure that container tightly sealed when not in use.
- Product is highly flammable in liquid and vapour form.
- Do not smoke or use near any sources of heat or ignition.
- Ensure solvent has evaporated from cloth or paper towel before disposal.(flammable)
- Do not spill onto any electrical components or switches.
- Product may dissolve certain plastics.
- Use in a well ventilated area away from any personal and children.
- Harmful if swallowed.
- Store well away from children, pets and untrained persons.
- Store in safe cool area.
- Product causes skin irritation.
- May cause respiratory irritation.
- Toxic to aquatic life.
- May cause dizziness.
- Keep container tightly sealed when not in use to avoid evaporation and contact with sources of ignition.

Safety, Storage and Disposal

Safety:

- Ensure good ventilation during application.
- **Keep out of reach of children!**
- Harmful if swallowed. If ingested, get medical help immediately and refer to SDS.
- Avoid contact with skin and eyes.
- If contact with skin occurs, wash off immediately with soap and water. Should adverse reaction occur, seek medical advice.
- If in contact with eyes, rinse immediately and thoroughly with plenty of clean water. Get medical assistance.
- Refer to SDS for hazard warnings and information on safe handling / use / transport / storage / disposal / emergency.


Storage:

- Unopened and correctly resealed containers must be kept out of direct sunlight and in dry conditions.
- **Store out of reach of children!**
- Unopened and correctly stored containers have a shelf life of 24 months.

Disposal:

- Do not dispose in drains, sewers or waterways.
- Dispose of waste contents and empty containers in accordance with local laws.
- **Keep used / empty containers away from children!**

Please refer to the SDS for the most current 'Handling and Storage' information.



The **STAG®** range of products are manufactured in Johannesburg (South Africa) in a factory equipped with solar panels. 75% of the of the total energy consumption of factory is supplied by the sun (April 2023 consumption data).



STAG™ TDS Technical Data Sheet

Terms of Use: This information is based on our present state of knowledge and is intended to provide general notes on our range of products and their uses. It should not be construed as a guarantee of specific properties of the products described, or the suitability for a particular application. If further information is required, please contact Liquid Colours.

The quality of our products undergoes specific and relevant tests related to their basic applications and end uses. The quality of our products is guaranteed under our General Conditions of Sale. Customers must independently determine the suitability for their intended products, uses or process. Liquid Colours makes no representation or warranty, expressed or implied, including merchantability or fitness for a particular use, regarding our products.

----- end document -----